

MOVAX

TAD-25

Telescopic Auger Drive (TAD), a new proud member of Movax™ family

Movax product family aims at providing a full line of excavator equipment for piling contractors. Movax is widely known as manufacturer of Side-Grip sheet pilers and tube drivers, which offer a unit for all excavators between 3 and 45 tons weight class. The new Telescopic Auger Drive offers Movax customer a possibility to complete wider range of contracts - piling work can now be completed with Movax products also in such areas where vibration is not allowed.

Also in cases where the ground conditions are difficult, Movax TAD-25 can help to complete the site. At the field of cast in situ piles Movax TAD-25 enables one to adopt new activities. Casing tubes can be driven with Movax tube driver and drill empty with Movax TAD-25. After concrete casting the casing can be removed again with Movax tube driver.





TAD-25

Telescopic Auger Drive

Various jobs – Versatile Movax

Movax TAD-25 is designed to fulfil the needs of Movax pile driving customers and is at its best with 24-29 ton excavators. One of the biggest benefits of TAD-25 is that it is connected to the end of the stick boom and adapters can be made for all quick couplers on the market. Therefore, compared with competitors who have to remove the stick boom completely, this creates conditions for a quick change between the different equipments and thus enables the completion of the foundation work at the jobsite with only one excavator.

With Movax Automatic Steering the drilling angle is under control and Auger functions can be utilised. Movax TAD-25 can drill holes into many angles from which vertical to 45° are the most typical. With a standard 600 mm auger Movax TAD-25 can reach 12 m depth and with an extension bar hole it is able to complete 15 m depth. Auger connection can be made according to customer's present augers standard connection being 75 mm square.



Technical data

Weight without adapter and auger (kg)	3100
Height without auger (mm)	3855
Depth (mm)	1673
Width (mm)	1013
Excavator class (ton)	24-29
Oil flow (l/min)	75-250
Max. return pressure (bar)	5
Pressure setting (bar)	320
Hole depth standard/extended (m)	12/15
Hole diameter (mm)	400-1200
Drill speed range (rpm)	22-74
Side tilt angle (o)	+/- 30
Torque (Nm)	15000
Auger pressing force (N)	15000
Auger pulling force (N)	30000

Unisto Oy

Productivity through innovation

Tölkkimäentie 10, FI-13130 Hämeenlinna, Finland
tel. +358-(0)3-628 070, fax +358-(0)3-616 1641
www.movax.com, email: marketing(a)unisto.fi

